



ISO 9001:2008 Registered

Style: PAC IX
Model# 70



Hood is constructed with an outer layer of P.B.I. Gold[®] and an inner layer of P.B.I.[®]

DESIGN – TWO PIECE with NOTCHED SHOULDER and SHOULDER INSERT

HEAD DESIGN

- LAYERS:** 2 ply *
- LENGTH:** From top of head to neck: 13 inches
- WIDTH:** Back seam to top of face: 9 inches
Back seam to bottom of head: 11 inches
- SIZING:** One size fits all. Do not modify, change, or alter your protective hood in any manner.
- * LAYERS** Head is constructed with an outer layer of P.B.I. Gold[®] and inner layer of P.B.I.[®]

BIB DESIGN

- LAYERS:** 2 ply *
- LENGTH:** 9 inches (front and back)
- NOTCHED SHOULDER DESIGN with INSERT:** From top of head to bottom of shoulder insert: 18 inches
- INSERT:** Bib has shoulder insert sewn in to give added shoulder protection
- * LAYERS** Bib is constructed with an outer layer of P.B.I. Gold[®] and inner layer of P.B.I.[®]

OVERALL HOOD LENGTH:

From top of head to bottom of apron: 22 inches

FACE OPENING MEASUREMENTS

- RELAXED:** 5 inches (UL requirement 4.7-5.7 inches)
 - STRETCHED:** 15 inches
- Face opening is sewn with 1/2 inch elastic.

CONSTRUCTION

- SEAMS:** All seams are merrow stitched then top and bottom covered with a 5-thread cover stitch for extended durability. All bottom edges are bound with binding.
- THREAD:** 100% Nomex[®]

PAC IX data sheet (cont.)

CARE

Machine wash warm with regular detergent – no chlorine bleach
Tumble dry low heat
DO NOT commercially dry clean

WARRANTY INFORMATION

Your protective hood is warranted by the manufacturer to be free from defects in material and workmanship. This warranty does not cover normal wear or unusual exposures. This warranty is in lieu of all other warranties, express or implied, including but not limited to, implied warranties or marketability and / or fitness for a particular purpose. The manufacturer shall not be liable for incidental or consequential damages.

CERTIFICATION

Meets or exceeds **NFPA 1971-2007 Edition** and is **UL Certified**. Meets or exceeds **Cal/OSHA Standards**.

MATERIALS

MATERIAL	CONTENT	CONSTRUCTION	WEIGHT	COLOR(s)
P.B.I. [®]	20% P.B.I. [®] / 80% Lenzing FR [®]	1 x 1 Circular Knit	Approx. 6.4 oz. / sq. yd.	Lt. Brown
P.B.I. Gold [®]	40% P.B.I. [®] / 60% Kevlar	1 x 1 Circular Knit	Approx. 7.5 oz. / sq. yd.	Mustard Yellow or Black

All weights and measurements are approximate.

P.O. Box 248 • Lehighton, PA • 18235
Phone: 610-377-6273 • Fax: 610-377-6221
e-mail: cs@majhoods.com • website: www.majesticfireapparel.com

HOODS AND MORE