



ISO 9001:2008 Registered



**Rayon/Kevlar**  
PAC IA – Style #10

**PAC IA**

**LAYERS:** 2 ply \*  
**LENGTH:** From top of head to bottom: 18 inches  
**WIDTH:** Back seam to top of face: 9 inches  
 Back seam to bottom of head: 10 inches  
**SIZING:** One size fits all. Do not modify, change, or alter your protective hood in any manner.

MATERIAL	CONTENT	CONSTRUCTION	WEIGHT	COLOR(s)
Rayon Kevlar	80% FR Rayon / 20% Black Kevlar	1 x 1 Circular Knit	Approx. 8.0 oz. / sq. yd.	Grey

**TEST RESULTS FROM UNDERWRITERS LABORATORIES**

	Rayon/Kevlar TEST RESULT	NFPA 1971 REQUIREMENT
<b>TPP (THERMAL PROTECTIVE PERFORMANCE)</b>	36.3 cal/cm <sup>2</sup> (as received) 40.9 cal/cm <sup>2</sup> (laundered)	Minimum 20
<b>MATERIAL BURST STRENGTH</b>	515.6	Minimum 225 N (51 lbf)
<b>CLEANING SHRINKAGE</b>	-3.6%	Maximum 5 % (either way)
+ = Grows ~ = Shrinks		

**CLEANING AND STORAGE**

Hoods maintain protective properties after machine washing.

- Machine wash only using regular detergent
- Water temperature not to exceed 130° F
- Do not use chlorine bleach or detergents containing chlorine
- Do not use fabric softeners or detergents containing fabric softeners
- Do not wring hood to dry. Squeeze hood to remove excess water.
- Shape and lay flat in a dry, cool, shaded location to dry.
- Or Tumble dry, low heat.
- Do not commercially dry clean.
- Do not store your hood in direct sunlight.

**WARRANTY INFORMATION**

Your protective hood is warranted to be free from defects in material or workmanship for one year. This warranty does not cover normal wear or unusual exposures. This warranty is in lieu of all other warranties, expressed or implied, including but not limited to, implied warranties of marketability and / or fitness for a particular purpose. Repair or replacement for breach of this warranty shall be the exclusive remedy available. Majestic Fire Apparel, Inc. shall not be liable for incidental or consequential damages.

**CERTIFICATION**

Meets or exceeds NFPA 1971-2007 Edition and is UL Certified. Meets or exceeds Cal/OSHA Standards. All weights and measurements are approximate.

P.O. Box 248 • Lehighton, PA • 18235  
 Phone: 610-377-6273 • Fax: 610-377-6221  
 Email: [cs@majesticfireapparel.com](mailto:cs@majesticfireapparel.com) • Website: [www.majesticfireapparel.com](http://www.majesticfireapparel.com)