



ISO 9001:2008 Registered

Style: PAC II  
Model# 50



DESIGN – TWO PIECE with NOTCHED SHOULDER

**HEAD DESIGN**

**LAYERS:** 2 ply  
**LENGTH:** From top of head to neck: 13 inches  
**WIDTH:** Back seam to top of face: 9 inches  
Back seam to bottom of head: 11 inches

**OVERALL HOOD LENGTH:**

From top of head to bottom of apron: 21 inches

**SIZING:**

One size fits all (universal size). Do not modify, change, or alter your protective hood in any manner.

**RELAXED:**

5 inches (UL requirement 4.7-5.7 inches)  
Face opening is sewn with 1/2 inch elastic.

**BIB DESIGN**

**LAYERS:** 2 ply  
**LENGTH:** 8 inches (front and back)  
**NOTCHED SHOULDER DESIGN:**  
From top of head to bottom of notched shoulder: 15 inches

**RELAXED:**

**STRETCHED:** 15 inches

**SEAMS:**

All seams are merrow stitched then top and bottom covered with a 5-thread cover stitch for extended durability. All bottom edges are bound with binding.

**THREAD:**

100% Nomex®

FACE OPENING MEASUREMENTS

CONSTRUCTION

**CLEANING AND STORAGE**

Hoods maintain protective properties after machine washing.

- Machine wash only using regular detergent
- Water temperature not to exceed 130° F
- Do not use chlorine bleach or detergents containing chlorine
- Do not use fabric softeners or detergents containing fabric softeners
- Do not wring hood to dry. Squeeze hood to remove excess water.
- Shape and lay flat in a dry, cool, shaded location to dry.
- Or Tumble dry, low heat.
- Do not commercially dry clean.
- Do not store your hood in direct sunlight.

**WARRANTY INFORMATION**

Your protective hood is warranted to be free from defects in material or workmanship for one year. This warranty does not cover normal wear or unusual exposures. This warranty is in lieu of all other warranties, expressed or implied, including but not limited to, implied warranties of marketability and / or fitness for a particular purpose. Repair or replacement for breach of this warranty shall be the exclusive remedy available. Majestic Fire Apparel, Inc. shall not be liable for incidental or consequential damages.

**CERTIFICATION**

Meets or exceeds NFPA 1971-2007 Edition and is UL Certified. Meets or exceeds Cal/OSHA Standards.

*All weights and measurements are approximate.*

P.O. Box 248 • Lehighton, PA • 18235

Phone: 610-377-6273 • Fax: 610-377-6221

EMAIL: [cs@majhoods.com](mailto:cs@majhoods.com) • Website: [www.majhoods.com](http://www.majhoods.com)