



ISO 9001:2008 Registered

Style: PAC III

Model# 60



DESIGN – TWO PIECE with NOTCHED SHOULDER and SHOULDER INSERT (for added shoulder protection)

HEAD DESIGN

LAYERS: 2 ply
LENGTH: From top of head to neck: 13 inches
WIDTH: Back seam to top of face: 9 inches
Back seam to bottom of head: 11 inches

BIB DESIGN

LAYERS: 2 ply
LENGTH: 8 inches (front and back)
NOTCHED SHOULDER DESIGN WITH INSERT:
From top of head to bottom of notched shoulder: 15 inches
INSERT: Bib with insert for added shoulder protection

OVERALL HOOD LENGTH:

From top of head to bottom of apron: 21 inches

SIZING: One size fits all. Do not modify, change, or alter your protective hood in any manner.

FACE OPENING MEASUREMENTS

RELAXED: 5 inches (UL requirement 4.7-5.7 inches)
Face opening is sewn with ½ inch elastic.

STRETCHED: 15 inches

CONSTRUCTION

SEAMS: All seams are merrow stitched then top and bottom covered with a 5-thread cover stitch for extended durability. All bottom edges are bound with binding.

THREAD: 100% Nomex[®]

CLEANING AND STORAGE

Hoods maintain protective properties after machine washing.

- Machine wash only using regular detergent
- Water temperature not to exceed 130° F
- Do not use chlorine bleach or detergents containing chlorine
- Do not use fabric softeners or detergents containing fabric softeners
- Do not wring hood to dry. Squeeze hood to remove excess water.
- Shape and lay flat in a dry, cool, shaded location to dry.
- Or Tumble dry, low heat.
- Do not commercially dry clean.
- Do not store your hood in direct sunlight.

WARRANTY INFORMATION

Your protective hood is warranted to be free from defects in material or workmanship for one year. This warranty does not cover normal wear or unusual exposures. This warranty is in lieu of all other warranties, expressed or implied, including but not limited to, implied warranties of marketability and / or fitness for a particular purpose. Repair or replacement for breach of this warranty shall be the exclusive remedy available. Majestic Fire Apparel, Inc. shall not be liable for incidental or consequential damages.

CERTIFICATION

Meets or exceeds **NFPA 1971-2007 Edition** and is **UL Certified**. Meets or exceeds Cal/OSHA Standards.
All weights and measurements are approximate.

P.O. Box 248 • Lehighton, PA • 18235

Phone: 610-377-6273 • Fax: 610-377-6221

EMAIL: cs@majesticfireapparel.com • WEBSITE: www.majesticfireapparel.com