

Ultra C6 PAC II~SVZ



ISO 9001:2008 Registered



Ultra C6 • Strategic Vent Zone (SVZ)



Our **Ultra C6 PAC II – Strategic Vent Zone Hood** Provides superior protection by combining Majestic’s **Ultra C6 & CarbonKnight fabrics** in an innovative new hood design which allows heat to escape without the risk of steam burn.

DESIGN – THREE PIECE with NOTCHED SHOULDER and FR FABRIC HEAD VENT

2 PLY HEAD DESIGN

LENGTH: From top of head to neck: 13 inches
WIDTH: Back seam to top of face: 9 inches
 Back seam to bottom of head: 11 inches

2 PLY VENT ZONE DESIGN

LENGTH: From top of head to neck: 13 inches
WIDTH: 3 inches

SIZING: One size fits all (universal size). Do not modify, change, or alter your protective hood in any manner.

FACE OPENING MEASUREMENTS

RELAXED: 5 inches (UL requirement 4.7-5.7 inches)
 Face opening is sewn with ½ inch elastic.
STRETCHED: 15 inches

2 PLY BIB DESIGN

LENGTH: 8 inches (front and back)
NOTCHED SHOULDER DESIGN: From top of head to bottom of notched shoulder: 15 inches

OVERALL HOOD LENGTH: From top of head to bottom of apron: 21 inches

CONSTRUCTION

SEAMS: All seams are merrow stitched then top and bottom covered with a 5-thread cover stitch for extended durability. All bottom edges are bound with binding. Sewn with 100% Nomex® thread.

MATERIAL	CONTENT	CONSTRUCTION	WEIGHT	COLOR(s)
Ultra C6	65% Oxidized Polyacrylonitrile (OPF)/ 35% artificial tri-blend	1 x 1 Circular Knit	Approx. 6.5 oz. / sq. yd.	Black
Ultra CarbonKnight Vent Zone	65% Oxidized Polyacrylonitrile (OPF)/ 35% artificial tri-blend	Thermal Knit	Approx. 6.5 oz. / sq. yd.	Black

CLEANING AND STORAGE

Hoods maintain protective properties after machine washing.

- Machine wash only using regular detergent
- Water temperature not to exceed 130° F
- Do not use chlorine bleach or detergents containing chlorine
- Do not use fabric softeners or detergents containing fabric softeners
- Do not wring hood to dry. Squeeze hood to remove excess water.
- Shape and lay flat in a dry, cool, shaded location to dry.
- Or Tumble dry, low heat.
- Do not commercially dry clean.
- Do not store your hood in direct sunlight.

WARRANTY INFORMATION

Your protective hood is warranted to be free from defects in material or workmanship for one year. This warranty does not cover normal wear or unusual exposures. This warranty is in lieu of all other warranties, expressed or implied, including but not limited to, implied warranties of marketability and / or fitness for a particular purpose. Repair or replacement for breach of this warranty shall be the exclusive remedy available. Majestic Fire Apparel, Inc. shall not be liable for incidental or consequential damages.

CERTIFICATION

Meets or exceeds NFPA 1971-2007 Edition and is UL Certified. Meets or exceeds Cal/OSHA Standards.

All weights and measurements are approximate.

P.O. Box 248 • Lehighton, PA • 18235

Phone: 610-377-6273 • Fax: 610-377-6221

EMAIL: cs@majhoods.com • Website: www.majhoods.com

HOODS AND MORE